## IN THE CLAIMS

Claims 1-54 were previously cancelled. Claims 55, 57, 64, 67, 70, 85, 88, 91, 97, 99 and 101-104 are currently amended. Claim 58 is currently cancelled. Claims 56, 59-63, 65, 66, 68, 69, 71-84, 86, 87, 89, 990, 92-96, 98 and 100 are carried forward, all as follows.

Claims 1-54 (Cancelled

55. (Currently Amended) A web draw-in device comprising:

a web folding apparatus including a superstructure;[[ ,]]

at least one former located in said web folding apparatus after, in a direction of paper web travel, said superstructure; and

a transverse cutting device adapted to <u>transversely cut</u> separate webs of material transported in said superstructure and folded at said former, said transverse cutting device being located after, in said direction of web travel, said at least one former;[[: and]]

at least one guide rail adapted to receive-a paper web leading end holding devices device and being usable to guide said paper the web leading end holding devices of material through said superstructure, along a route of travel of the webs web of material in said web folding apparatus to draw in the webs of material through said web folding apparatus, said guide rail extending through from said superstructure, past into said former and past, in said direction of web travel, to at least an inlet to said transverse cutting device[[.]]; and

at least one twisted guide rail section in said guide rail, said at least one twisted guide rail section in said guide rail being located adjacent said at least one former.

- 56. (Previously Presented) The device of claim 55 further including a plurality of guide elements joining said guide rail before, in said direction of web travel, said transverse cutting device and after said at least one former.
- 57. (Currently Amended) The device of claim 55 further including a paper web leading end clipping device before said transverse cutting device and further including a guide rail curved section after said clipping device and before <u>said-an</u> inlet to said transverse cutting device.
- 58. (Cancelled)
- 59. (Previously Presented) The device of claim 55 wherein said guide rail is displaceable in a cutting direction of said transverse cutting device.
- 60. (Previously Presented) The device of claim 55 further including an extendable guide rail section before, in said direction of web travel, said former, said guide rail being extendable in said direction of web travel.
- 61. (Previously Presented) The device of claim 55 wherein said guide rail has an articulated section between an inlet to said former and said transverse cutting device.
- 62. (Previously Presented) The device of claim 61 further including a plurality of cuts in said guide rail and forming said articulated section of said guide rail.

- 63. (Previously Presented) The device of claim 55 wherein a spacing distance from said guide to the paper web is constant from an inlet roller of said former to an exit lip of said former.
- 64. (Currently Amended) The device of claim 62 wherein said guide rail includes a bottom and spaced side walls defining a groove in which said holding devices are device is guided, said cuts extending through at least one of said side walls.
- 65. (Previously Presented) The device of claim 55 wherein said transverse cutting device includes a cutter cylinder.
- 66. (Previously Presented) The device of claim 55 wherein said transverse cutting device includes a cylinder with a holding system.
- 67. (Currently Amended) The device of claim 55 wherein said transverse cutting device includes a folding blade cylinder.
- 68. (Previously Presented) The device of claim 55 wherein said guide rail extends through a gap formed by a cutter cylinder and a folding blade cylinder on said transverse cutting device.
- 69. (Previously Presented) The device of claim 55 further including a paper web leading end clipping device before, in said direction of web travel, said transverse cutting device.

- 70. (Currently Amended) The device of claim 69 further including <u>said</u> an inlet to said transverse cutting device <u>being</u> arranged in said direction of web travel after said clipping device.
- 71. (Previously Presented) The device of claim 70 wherein said inlet to said transverse cutting device is positioned vertically beneath said clipping device.
- 72. (Previously Presented) The device of claim 70 wherein said guide rail has a curved section located between said clipping device and said inlet to said transverse cutting device, said guide rail curved section extending past said inlet of said transverse cutting device.
- 73. (Previously Presented) The device of claim 55 further including a holding element storage device located at an extension of said guide rail and after said former.
- 74. (Previously Presented) The device of claim 73 wherein said storage device is one of a spiral-shaped and a helix-shaped rail element.
- 75. (Previously Presented) The device of claim 73 further including a separating device usable to separate web leading ends from said holding devices and located before, in said direction of web travel, said storage device.
- 76. (Previously Presented) The device of claim 75 wherein said guide rail includes a curved section intermediate said separating device and said storage device.

- 77. (Previously Presented) The device of claim 55 further including a roll changer located before, in said direction of web travel, said web folding apparatus and wherein said quide rail extends continuously from said roll changer into said folding apparatus.
- 78. (Previously Presented) The device of claim 55 further including a plurality of web travel routes, each of said plurality of web travel routes being usable to conduct a paper web through said superstructure to said transverse cutting device.
- 79. (Previously Presented) The device of claim 78 further including several guide elements, which each extend along one of said routes, each of said several guide elements joining said guide rail before, in said direction of web travel, said transverse cutting device.
- 80. (Previously Presented) The device of claim 79 wherein said several guide elements join said guide rail after, in said direction of web travel, said at least one former at junction points.
- 81. (Previously Presented) The device of claim 80 further including a shunt at each junction point of one of said guide elements and said guide rail.
- 82. (Previously Presented) The device of claim 80 further including a glue-preparation device arranged on at least one of said routes before, in said direction of web travel, a respective one of said junction points.
- 83. (Previously Presented) The device of claim 82 wherein each said glue-preparation device is one of an adhesive tape dispenser and a glue dispenser.

- 84. (Previously Presented) The device of claim 83 further including a web start sensor assigned to each said glue-preparation device.
- 85. (Currently Amended) The device of claim 55 further including a finite length chain in said at least one guide rail-holding device.
- 86. (Previously Presented) The device of claim 85 wherein said finite length chain adapted to be curved transversely to said direction of web travel.
- 87. (Previously Presented) The device of claim 86 wherein said finite length chain includes chain rollers having longitudinal axes and further wherein an extension of said longitudinal axes intersect at a point defining a radius of curvature of less than 1000 mm.
- 88. (Currently Amended) The device of claim 55 further including a plurality of said formers and a separate one of said guide <u>rails\_rail</u> being conducted <u>past\_along</u> each one of said plurality of formers.
- 89. (Previously Presented) The device of claim 88 wherein first and second ones of said formers are arranged adjacent each other and further wherein a first guide rail is arranged on a first side of said first former and a second guide rail is arranged on a second side of said second former.
- 90. (Previously Presented) The device of claim 89 wherein said first side of said first former and said second side of said second former are not adjacent each other.

- 91. (Currently Amended) The device of claim 55 wherein said <u>at least one</u> former has a former side and further wherein said at least one guide rail extends along said former side.
- 92. (Previously Presented) The device of claim 91 wherein said former side is inclined at an acute angle with respect to said direction of web travel.
- 93. (Previously Presented) The device of claim 77 further including at least two roll changers and wherein a separate of one said guide rails extends from each of said at least two roll changers.
- 94. (Previously Presented) The device of claim 91 wherein said guide rail is spaced at a distance from said former side.
- 95. (Previously Presented) The device of claim 55 wherein said at least one former has a former lateral edge and further wherein said at least one guide rail extends parallel to said at least one former lateral edge.
- 96. (Previously Presented) The device of claim 55 further including a chain element in said at least one guide rail, said chain element being adapted to be curved transversely to said direction of web travel.
- 97. (Currently Amended) A method for drawing in at least one web of material including:

providing a roll changer supporting a first web of material;

providing a folding apparatus including a superstructure, at least one former located in a direction of web travel after said superstructure, and a transverse cutting

device usable for separating webs of material transported through said superstructure and located at said former, into individual products;

locating said transverse cutting device in said folding apparatus after, in said direction of web travel, said at least one former;

providing a guide rail; having

<u>providing-a displaceable</u> paper web leading end holding <u>devices device</u> <u>being displaceable</u> in said guide rail;

providing at least one twisted guide rail section in said guide rail;

locating said guide rail extending from said roll changer through at least one printing group and through said folding apparatus;

one former in said folding apparatus;

fastening a leading end of a first web of material to <u>one of</u> said holding <u>devices device</u> at said roll changer;

using said holding device for transporting said <u>leading end of said</u> first web of material from said roll changer through said at least one printing group, over said at least one former and <u>at least to an inlet to through</u> said transverse cutting device; and

separating said leading end of said first web from said holding device after transporting said leading end of said first web of material to, in said direction of web travel, said transverse cutting device.

98. (Previously Presented) The method of claim 97 further including providing at least one guide element, joining said at least one guide element to said guide rail at a first junction point, conducting a second web of material to said first junction point along said at least one guide element, joining said second web of material to said first web of material at said junction

point and conducting said joined first and second webs of material together to said transverse cutting device.

- 99. (Currently Amended) The method of claim 98 further including joining said second web of material to said first web of material after <u>passing</u> said holding device <u>past-hased-said</u> junction point.
- 100. (Previously Presented) The method of claim 98 further including conducting said first and second webs of material to said transverse cutting device using said guide rail.
- 101. (Currently Amended) The method of claim 97 further including providing a web leading end clipping device located before, in said direction of web travel, <u>an inlet to</u> said transverse cutting device, using said clipping device <u>for-and</u> clipping said leading ends of said webs of materials and directing said clipped leading ends into said <u>inlet to said</u> transverse cutting device.
- 102. (Currently Amended) The method of claim 101 further including locating said inlet to said transverse cutting device in alignment with said clipping device.
- 103. (Currently Amended) The method of claim 97 further including providing a holding device storage device connected to said guide rail, initially-and using said storage devices for initially collecting said holding devices and at the conclusion of a printing process returning said holding devices along said-collecting said holding devices and for then returning said holding device along said-guide rail back to initial positions.

104. (Currently Amended) The method of claim 97 further including providing a second roll changer, fastening a second web leading end to a second holding device at said second roll changer, and using said second holding device and transporting said second web of material through at least one printing group, over at least one former and through said transverse cutting device, and cutting said second web of material off-of said second holding device at-after, in said direction of web travel, at least said inlet to said transverse cutting device to-through-which said first web of material was conducted using-on said first holding device.